

Serial No.: 10/017,103

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings of claims in the application.

**Listing of Claims:**

1 (currently amended). A method of demodulating a received signal corresponding to a plurality of transmitted symbol sequences originating from both a first user and a second user, the method comprising:

initializing, using known pilot symbols for the first user and the second user, a first-user symbol sequence corresponding to the first user and a second-user symbol sequence corresponding to the second user and channel estimates for the first user and the second user wherein the first user and the second user can be asynchronous ; and jointly detecting the first-user symbol sequence and the second-user symbol sequence using, at each of a plurality of iterations previous first and second user symbol sequences and the channel estimates for the first user and the second user, and based on the use of transmit diversity by at least one of the first user and the second user and on a pulse shape component and applied to symbols from prior iterations.

2 (original). The method of claim 1 further comprising updating the channel estimates prior to each of the plurality of iterations.

3 (original). The method of claim 1 wherein channel estimates are obtained using alternate pilot channels in a code division multiplexed access (CDMA) system.

4-6 (cancelled).

4 (currently amended). A method of demodulating a received signal corresponding to a plurality of transmitted symbols originating from both a first user and a second user, the method comprising:

Serial No.: 10/017,103

initializing a pulse-shape component and, using known pilot symbols for the first user and the second user, a first-user symbol corresponding to the first user and a second-user symbol corresponding to the second user and channel estimates for the first user and the second user wherein the first user and the second user can be asynchronous;

jointly detecting a first-user symbol and a second-user symbol at a current symbol time using previous first and second user symbols and channel estimates for the first user and the second user and the pulse-shape component, and based on the use of transmit diversity by at least one of the first user and the second user; and

if additional symbol times remain, jointly detecting the first user symbol and the second user symbol at a next symbol time.

~~5~~ ~~8~~ (original). The method of claim ~~7~~ <sup>4</sup> further comprising:

predicting the channel estimates for a next symbol time, at least in part through the use of channel tracking; and

updating the first-user symbol and the second-user symbol.

9-10 (cancelled).

~~11~~ <sup>2</sup> (currently amended). Apparatus for demodulating a received signal corresponding to a plurality of transmitted symbol sequences originating from both a first user and a second user, the apparatus comprising:

means for initializing, using known pilot symbols for the first user and the second user, a first-user symbol sequence corresponding to the first user and a second-user symbol sequence corresponding to the second user wherein the first user and the second user can be asynchronous;

means for initializing channel estimates for the first user and the second user, using the known pilot symbols for the first user and the second user; and

means for iteratively and jointly detecting the first-user symbol sequence and the second-user symbol sequence using previous first and second user symbol

Serial No.: 10/017,103

sequences and the channel estimates for the first user and the second user, and based on the use of transmit diversity by at least one of the first user and the second user and on a pulse shape component ~~applied to~~ and symbols from prior iterations.

12 (cancelled).

~~13~~ <sup>8</sup> (currently amended). A receiving system operable to demodulate a received signal corresponding to a plurality of transmitted symbol sequences originating from both a first user and a second user, the system comprising:

a channel estimation unit operable to produce channel estimates for the first user and the second user, using known pilot symbols for the first user and the second user, and

a detector unit operatively connected to the channel estimation unit, the detector unit operable to jointly detect a first-user symbol sequence and a second-user symbol sequence using previous first and second user symbol sequences, the known pilot symbols for the first user and the second user, and the channel estimates for the first user and the second user, wherein the first user and the second user can be asynchronous, and based on the use of transmit diversity by at least one of the first user and the second user and on a pulse shape component ~~applied to~~ and symbols from prior iterations.

~~14~~ <sup>9</sup> (original). The system of claim ~~13~~ <sup>8</sup> wherein the channel estimation unit updates the channel estimates prior to each of a plurality of iterations.

~~15~~ <sup>10</sup> (original). The system of claim ~~13~~ <sup>8</sup> wherein the channel estimation unit obtains channel estimates using alternate pilot channels in a code division multiplexed access (CDMA) system.

16-18 (cancelled).

Serial No.: 10/017,103

~~11~~  
~~19~~ (currently amended). A receiving system operable to demodulate a received signal corresponding to a plurality of transmitted symbols originating from both a first user and a second user, the system comprising:

a channel estimation unit operable to produce channel estimates for the first user and the second user, using known pilot symbols for the first user and the second user, and

a detector unit including a symbol update unit, the detector unit operatively connected to the channel estimation unit, the detector unit operable to jointly detect a first-user symbol and a second-user symbol at specific symbol times using previous first and second user symbols, the known pilot symbols for the first user and the second user, and the channel estimates for the first user and the second user, as well as a pulse-shape component and symbols from prior iterations, wherein the first user and the second user can be asynchronous, and based on the use of transmit diversity by at least one of the first user and the second user;

and wherein both the symbol update unit and channel estimation unit further comprise reformulation operators, conjugation operators connected to the reformulation operators, and multipliers and adders interconnected with the reformulation operators and conjugation operators.

20-21 (cancelled).

~~12~~  
~~22~~ (original). The system of claim ~~20~~ wherein the channel estimation logic predicts channel estimates at least in part through channel tracking.

23-26 (cancelled).

~~14~~  
~~27~~ (currently amended). A mobile terminal comprising:

a processor system for controlling the operation of the mobile terminal;

Serial No.: 10/017,103

a radio block operable to transmit signals, and also to receive signals corresponding to a plurality of transmitted symbols originating from both a first user and a second user;

baseband logic operatively connected to the radio block and the processor system, the baseband logic further comprising a channel estimation unit operable to produce channel estimates for the first user and the second user, using known pilot symbols for the first user and the second user, and a detector unit operatively connected to the channel estimation unit, the detector unit operable to jointly detect first-user symbols and second-user symbols based on the channel estimates for the first user and the second user, and using the known pilot symbols for the first user and the second user, wherein the first user and the second user can be asynchronous, and based on the use of transmit diversity by at least one of the first user and the second user and on a pulse shape component applied to and symbols from prior iterations.

~~15~~ 28 (original). The mobile terminal of claim ~~27~~ <sup>14</sup> wherein the channel estimation unit performs block estimation and the detector unit performs block detection of the first user symbols and the second user symbols.

~~16~~ 29 (original). The mobile terminal of claim ~~27~~ <sup>14</sup> wherein the channel estimation unit performs recursive estimation using channel tracking and the detector unit performs recursive detection of the first user symbols and the second user symbols.

30 (cancelled).

~~18~~ 31 (original). The mobile terminal of claim ~~27~~ <sup>14</sup> wherein the channel estimation unit produces channel estimates by referring to alternate pilot channels in a code division multiplexed access (CDMA) system.

Serial No.: 10/017,103

~~19~~ 32 (original). The mobile terminal of claim ~~14~~ 27 wherein the detector unit further comprises a symbol update unit, and the symbol update unit and the channel estimation unit each further comprise:

reformulation operators;

conjugation operators connected to the reformulation operators; and

multipliers and adders interconnected with the reformulation operators and

conjugation operators.

~~12~~ 33 (original). The mobile terminal of claim ~~16~~ 29 wherein the detector unit further comprises a symbol update unit, and the symbol update unit and the channel estimation unit each further comprise:

reformulation operators;

conjugation operators connected to the reformulation operators; and

multipliers and adders interconnected with the reformulation operators and

conjugation operators.

34 (cancelled).

~~6~~ 35 (previously presented). The method of claim ~~4~~ 7 where the jointly detecting can be accomplished at least in part by estimating the plurality of symbols out of natural order.

36 (cancelled).

~~13~~ 37 (previously presented). The receiving system of claim ~~11~~ 18 wherein the detector unit is further operable to detect the first user symbol and the second user symbol out of natural order.

38 (cancelled).

Serial No.: 10/017,103

<sup>20</sup>  
~~39~~ (previously presented). The mobile terminal of claim ~~27~~<sup>14</sup> wherein the detector unit is further operable to detect the first user symbol and the second user symbol out of natural order.